

PRS-150T 電子洛氏硬度計 ELECTRONIC ROCKWELL SCLEROMETER

- 1.隱藏式荷重置放,美觀大方,凌駕進口產品。
- 2.精準紮實的結構設計,配合電動式壓放荷重功能,提高測試穩定性。
- 3.具備荷重保持定時功能或設定成手動模式。
- 4.LCD觸控螢幕操作得心應手。
- 5.內建圓弧、多點補正曲線及硬度換算等功能。
- 6.可搭配微型印表機,同步列印測試數據(選配)。
- 7.機台防傾設計。

- 1.Hidden load placement, beautiful appearance, superior than imported products.
- 2.Precise and solid structure design with the function of electric pressing /releasing load enhances the testing stability.
- 3.Equipped with load control and timing function.
- 4.A LCD monitor for easy operation.
- 5.Built arc, multi-point correction curve and hardness conversion functions.
- 6.Can be paired up with a micro-printer to print out test data concurrently (optional.)
- 7.Anli-tilt design for the machine base.

規範 Specification

單位:公釐 Unit:mm

型號 MODEL	PRS-150T	
基準荷重 Standard Load	3 kgf (29.4N)	10 kgf (98.07N)
試驗荷重 Testing Load	15 kgf (147.1N)	60 kgf (588.4N)
	30 kgf (294.2N)	100 kgf (980.7N)
	45 kgf (441.3N)	150 kgf (1471N)
荷重方式 Load Mode	自動方式 (負荷、保持、除荷), 時間可設定 Automatic Mode (Load , Hold , Unload), Time Can be Set	
荷重保持時間 Load Duration	2 ~ 120 秒 (Sec.) (可任意設定Can be Set Arbitrarily)	
荷重變換 Load Range	觸控切換自動變荷 Touch Switch Load Automatically	
工件容許高度 Object Height Allowed	165 mm	
喉深 Throat Depth	120 mm	
硬度測試方式 Hardness Test Mode	自動打點方式 Automatic Dotting Mode	
顯示 Display	硬度值, 試驗條件, 硬度換算值 Hardness Value, Test Conditions, Hardness Conversion Value	
語言 Language	繁體中文、簡體中文、英文 Traditional Chinese , Simplified Chinese , English	
電源 Power	AC 100 ~ 240 V 60 / 50 Hz 1phase	
傳輸 Transmission	RS-232、RS-485、USB、Printer	
機械尺寸 Dimension	D 480 x W 180 x H 630	
機械重量 Net Weight	55 kg	

PRS-150T



標準配件 Accessories

- 1.鑽石測頭Diamond probe : 1 pc
- 2.1 / 16"鋼珠測頭 Steel ball probe : 1 pc
- 3.64mm平面鉗座Horizontal drilling base : 1 pc
- 4.V型鉗座 V - shape drilling base : 1 pc
- 5.內六角扳手Embedded hexagonal wrench : 1 pc (2mm)
- 6.水平儀 Gradiener : 1 pc
- 7.防塵套 Dust cover : 1 pc
- 8.電源線 Power cable : 1 pc
- 9.標準試片 Standard testing patch :
HRC 30 x 1 pc / HRC 60 x 1 pc /
HRB 90 x 1 pc / HR30N 78 x 1pc /
HR30T 75 x 1 pc